




Elsan Elektrik San. ve Tic. A.Ş
 Etiler Mah. 1458 Cad. No:40
 06790 Etimesgut / Ankara / TÜRKİYE
 Tlf: +90 312 244 09 94 F: +90 312 243 14 38
 Mail: info@emtas.com.tr / Web Sayfası: www.emtas.com.tr



TECHNICAL SPECIFICATION SHEET

THREE PHASES SQUIRREL CAGE ASYNCHRONOUS MOTOR

Type	NMST 355L 8	
Protection Class	IP65	
Duty Type / Service Factor	S1	1.0
Insulation Class	H	
Construction Type /Frame	V5-V6-B6-B7-B8	V1-V3
Altitude / Ambient temperature	V1-V3	40 °C




PERFORMANCE DATA (FULL LOAD)

Output Rated (kW)	Speed (1/min)	Voltage (V)	Frequency (Hz)	Current (A)	Efficiency (%)	Power Factor (CosØ)	Rated Torque MN (Nm)	Starting Current IK/IN	Starting Torque MK/MN	Breakdown Torque MD/MN	Moment of Inertia Jmot kgm2
200	740	400	50	396.3	94.6	0.77	2581.1	5.4	1.8	2.0	8.2159

CHARACTERISTIC DATA

Frame	Pik Cast. (GG20)	BEARINGS	Drive End Bearing		Non Drive End Bearing		
Front-Back Cover	Pik Cast. (GG20)		Standart	6322		6321	
Foot	Sfero Casting		Heavy Duty	NU 322		6321	
Fan		Special Equipment	Brake	Forced ventilation	Heater	Encoder	Heat Sensor
Terminal Box	Pik Casting		---	---	---	---	---
Cable Gland	Pik Casting	Colour	RAL 6028-Yesil		Weight (kg)		1850



DIMENSIONS (B3-B5-V5-V6-B6-B7-B8)

B3										B5							Common Dimensions										
H	A	B	C	AB	AC	AD	BB	HC	HD	K	P	N	M	S	D.S	T.	LA	LB	LC	L	ØD	E	F	GA	GD	DB	R
355L	610	630	254	718	700	552	800	705	838	28	800	680	740	24	8		25	1667	1147	100	210	28	106	16	M24	2 x M63	