




Elsan Elektrik San. ve Tic. A.Ş
Etiler Mah. 1458 Cad. No:40
06790 Etimesgut / Ankara / TÜRKİYE
Tlf: +90 312 244 09 94 F: +90 312 243 14 38
Mail: info@emtas.com.tr / Web Sayfası: www.emtas.com.tr



TECHNICAL SPECIFICATION SHEET

THREE PHASES SQUIRREL CAGE ASYNCHRONOUS MOTOR

Type	NMST 160M 2	
Protection Class	IP55	
Duty Type / Service Factor	S2 240 dak	1.0
Insulation Class	F	
Construction Type /Frame	V5-V6-B6-B7-B8	V1-V3
Altitude / Ambient temperature	V1-V3	40 °C





PERFORMANCE DATA (FULL LOAD)

Output Rated (kW)	Speed (1/min)	Voltage (V)	Frequency (Hz)	Current (A)	Efficiency (%)	Power Factor (CosØ)	Rated Torque MN (Nm)	Starting Current IK/IN	Starting Torque MK/MN	Breakdown Torque MD/MN	Moment of Inertia Jmot kgm2
15	2923	400	50	27.7	88.7	0.88	49.0	6.3	2.8	3.2	0.0339

CHARACTERISTIC DATA

Frame	Pik Cast. (GG20)	BEARINGS			Drive End Bearing		Non Drive End Bearing	
Front-Back Cover	Pik Cast. (GG20)		Standart		6309 ZZ		6309 ZZ	
Foot	Sfero Casting		Heavy Duty		NU 309		6309 ZZ	
Fan	Plastik	Special Equipment	Brake	Forced ventilation	Heater	Encoder	Heat Sensor	
Terminal Box	Casting		---	---	---	---	---	
Cable Gland	Casting	Colour	RAL 6028-Yesil			Weight (kg)		112



DIMENSIONS (B3-B5-V5-V6-B6-B7-B8)

B3											B5							Common Dimensions												
H	A	B	C	AB	AC	AD	BB	HC	HD	K	P	N	M	S	D.S	T.	LA	LB	LC	L	ØD	E	F	GA	GD	DB	R			
160M	254	210	108	318	310	236	304	315	373	15	350	250	300	19	4		18		729	613	42	110	12	45	8	*	2 x Pg21			