



Elsan Elektrik San. ve Tic. A.Ş
 Etiler Mah. 1458 Cad. No:40
 06790 Etimesgut / Ankara / TÜRKİYE
 Tlf: +90 312 244 09 94 F: +90 312 243 14 38
 Mail: info@emtas.com.tr / Web Sayfası: www.emtas.com.tr



TECHNICAL SPECIFICATION SHEET

THREE PHASES SQUIRREL CAGE ASYNCHRONOUS MOTOR		
Type	NMST 100L 8	
Protection Class	IP55	
Duty Type / Service Factor	S2 240 dak	1.0
Insulation Class	F	
Construction Type /Frame	V5-V6-B6-B7-B8	V1-V3
Altitude / Ambient temperature	V1-V3	40 °C



PERFORMANCE DATA (FULL LOAD)

Output Rated (kW)	Speed (1/min)	Voltage (V)	Frequency (Hz)	Current (A)	Efficiency (%)	Power Factor (CosØ)	Rated Torque MN (Nm)	Starting Current IK/IN	Starting Torque MK/MN	Breakdown Torque MD/MN	Moment of Inertia Jmot kgm2
0.75	689	400	50	2.8	61.0	0.64	10.4	3.0	1.6	1.8	0.0073

CHARACTERISTIC DATA

Frame	Pik Cast. (GG20)	BEARINGS	Drive End Bearing		Non Drive End Bearing		
Front-Back Cover	Pik Cast. (GG20)		Standart	6206 ZZ		6206 ZZ	
Foot	Sfero Casting		Heavy Duty	NU 206		6206 ZZ	
Fan	Plastik	Special Equipment	Brake	Forced ventilation	Heater	Encoder	Heat Sensor
Terminal Box	Pik Casting		---	---	---	---	---
Cable Gland	Pik Casting		Colour	RAL 6028-Yesil		Weight (kg)	21



DIMENSIONS (B3-B5-V5-V6-B6-B7-B8)

B3										B5							Common Dimensions										
H	A	B	C	AB	AC	AD	BB	HC	HD	K	P	N	M	S	D.S	T.	LA	LB	LC	L	ØD	E	F	GA	GD	DB	R
100L	160	140	63	200	194	138	175	197	-	12	250	180	215	15	4		14		453	386	28	60	8	31	7	*	2 x Pg13.5