



ELSAN Elektrik San. ve Tic. A.Ş.
 Etiler Mah. 1458. Cad. No:40
 06790 Etimesgut / Ankara / TÜRKİYE
 T: +90 312 244 09 94 F: +90 312 243 14 38
 M: info@emtas.com.tr W: www.emtas.com.tr



TECHNICAL SPECIFICATION SHEET

THREE PHASES SQUIRREL CAGE ASYNCHRONOUS MOTORS

| | | | |
|--------------------------------|------------|------------|---|
| Type | NMSF 315S6 | | |
| Protection Class | IP 65 | | |
| Duty Type / Service Factor | S1 | 1.0 | |
| Insulation Class | H | | |
| Construction Type /Frame | B3/ 315S6 | | |
| Altitude / Ambient temperature | 1000 m | 40 C° | |
| Customer / Date / Order Number | - | 12.03.2026 | - |



PERFORMANCE DATA (FULL LOAD)

| Rated Output (kW) | Rated Speed (1/min) | Voltage (V) | Frequency (Hz) | Current (A) | Efficiency (%) | Power Factor (Cos φ) | Rated Torque MN (Nm) | Starting Current IK/IN | Starting Torque MK/MN | Breakdown Torque MD/MN | Moment of Inertia Jmot (kgm²) |
|-------------------|---------------------|-------------|----------------|-------------|----------------|----------------------|----------------------|------------------------|-----------------------|------------------------|-------------------------------|
| 75 | 990 | 400 | 50 | 133,5 | 95,4 | 0,85 | 723,5 | 6,0 | 1,8 | 2,3 | 2,262 |

CHARACTERISTIC DATA

| | | | | | | | |
|-------------------------|----------------------|-------------------|------------------|--------------------|--------------------------|-------------------|-----------------------|
| Frame | Cast Iron (GG20) | Bearings | Standart | | | Drive End Bearing | Non Drive End Bearing |
| End Shield - DE and NDE | Cast Iron (GG20) | | Heavy Duty | | | 6319 | 6318 |
| Foot | Ductile Iron (GGG40) | | | | | NU 319 | - |
| Fan | Aluminium | Special Equipment | Brake | Forced ventilation | Heater | Encoder | Heat sensor |
| Terminal box | Cast Iron (GG20) | | 3200 Nm brake | --- | <input type="checkbox"/> | | --- |
| Cable Gland | Brass 2 x Pg48 | Colour | RAL 6028 - Green | | | Weight (kg) | 993 |



DIMENSIONS (mm) (B3-B5-V1-V5-V6-B6-B7-B8-B35)

| B3 | | | | | | | | | | B5 | | | | | | | | | | Common Dimensions | | | | | | | | | |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------|-------|-------|------|-----------|-----|------|-----|--------|-------------------|------|-------|------|------|------|-----|----------|--|--|
| H | A | B | C | AB | AC | AD | BB | HC | HD | K | P | N | M | S | Hole Pcs. | T | LA | LB | LC | L | ØD | E | F | GA | GD | DB | R | | |
| 315,0 | 508,0 | 406,0 | 216,0 | 620,0 | 612,0 | 501,0 | 500,0 | 621,0 | 682,0 | 28,0 | 660,0 | 550,0 | 600,0 | 24,0 | 8,0 | 6,0 | 24,0 | --- | 1556,0 | 1378,0 | 85,0 | 170,0 | 22,0 | 90,0 | 14,0 | M20 | 2 x Pg48 | | |

Important Note : Values provided in this datasheet represent the preliminary design values. Please keep in mind that these values might vary for the final product, due to technical requirements.