




ELSAN Elektrik San. ve Tic. A.Ş.
Etiler Mah. 1458. Cad. No:40
06790 Etimesgut / Ankara / TÜRKİYE
T: +90 312 244 09 94 F: +90 312 243 14 38
M: info@emtas.com.tr W: www.emtas.com.tr



TECHNICAL SPECIFICATION SHEET

THREE PHASES SQUIRREL CAGE ASYNCHRONOUS MOTORS

Type	NMSC 200L		
Protection Class	IP55		
Duty Type / Service Factor	S1	1.0	
Insulation Class	H		
Construction Type /Frame	B35/ 200L		
Altitude / Ambient temperature	1000 m	40 C°	
Customer / Date / Order Number	-	10.08.2026	-




PERFORMANCE DATA (FULL LOAD)

Rated Output (kW)	Rated Speed (1/min)	Voltage (V)	Frequency (Hz)	Current (A)	Efficiency (%)	Power Factor (Cos φ)	Rated Torque MN (Nm)	Starting Current IK/IN	Starting Torque MK/MN	Breakdown Torque MD/MN	Moment of Inertia Jmot (kgm²)
16-26	723 1452	400	50	41,0 50,0	91,2	0,68 0,92	211,3 171,0	3,8 5,4	1,9 2,0	2,8	0,130

CHARACTERISTIC DATA

Frame	Cast Iron (GG20)	Bearings				Drive End Bearing		Non Drive End Bearing
End Shield - DE and NDE	Cast Iron (GG20)		Standart			6313 ZZ		6313 ZZ
Foot	Ductile Iron (GGG40)		Heavy Duty			-		-
Fan	Plastic	Special Equipment	Brake	Forced ventilation	Heater	Encoder		Heat sensor
Terminal box	Cast Iron (GG20)		---	---	☐	---		---
Cable Gland	PA6.6 2 x Pg29	Colour	RAL 6028 - Green			Weight (kg)		254



DIMENSIONS (mm) (B3-B5-V1-V5-V6-B6-B7-B8-B35)

B3											B5								Common Dimensions										
H	A	B	C	AB	AC	AD	BB	HC	HD	K	P	N	M	S	Hole Pcs.	T	LA	LB	LC	L	ØD	E	F	GA	GD	DB	R		
200,0	318,0	305,0	133,0	400,0	385,0	319,0	365,0	394,0	460,0	19,0	400,0	300,0	350,0	19,0	4,0	5,0	18,0	649,0	876,0	759,0	55,0	110,0	16,0	59,0	10,0	*	2 x Pg29		

Important Note : Values provided in this datasheet represent the preliminary design values. Please keep in mind that these values might vary for the final product, due to technical requirements.